


# PD2SYS-96 SERIES

# **HEATED DISPLAY SYSTEMS**



PD2SYS-96

• HALO HEAT ... a controlled, uniform heat source that gently holds and surrounds food for better appearance, taste, and longer holding life.



- $\bullet$  Expandable system to meet your specific requirements.
- Matches profile of leading refrigerated display case.

#### • HOT DISPLAY CASE

- Curved glass styling.
- Displays hot food without condensation on glass.
- Thermostatically controlled heat source radiates from the base of the display case in multiple heat zones.
- Overhead light zones with shatterproof coated bulbs.
- Holds a full range of standard (gastronorm) pan sizes, full-size or half-size sheet pans.
- Tempered sliding glass doors reflect heat back into the products and mirror the display to enhance merchandising effect.

#### • DECORATOR BASE

Standard black painted front and end panels.

The display case is constructed of 18 gauge, non-magnetic stainless steel and is mounted directly on top of two pedestal risers. A curved, tempered glass front encloses the display case and can be lifted to a 90 degree angle for easy cleaning. Removable, sliding glass doors on the operator side are included. Sliding door tracks have a "clean sweep" cutout allowing for easy cleaning and crumb removal. Framed end glass with rubber gasket material protects glass edges from chipping and breakage. The base is divided into three (3) individually managed heat zones with each zone controlled by a separate thermostat with a range of 1 through 10 and heat-on indicator light. Overhead lights are controlled by ON/OFF switches in three (3) light zones. Two (2) 125V plug outlets are available as an option on 120/208-240V units only.

☐ **PD2SYS-96** - 96" (2438mm) length



#### **FACTORY INSTALLED OPTIONS**

- Panel Color Choices
  - **⇒**Specify color choice:
  - ☐ Black, standard
  - ☐ Stainless Steel, optional
  - ☐ Custom Color, optional




W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.




# PD2SYS-96 SERIES

# **HEATED DISPLAY SYSTEMS**



**PD2SYS Profile** 



# INSTALLATION REQUIREMENTS

Display case must be installed level. The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.

WEIGHT					
MODEL	NET	SHIP			
PD2SYS-96	740 lb (336 kg)	885 lb (401 kg)			
CRATED DIMENSIONS (EST.): H X W X D					
107" x 51" x 57" (2718mm x 1295mm x 1148mm)					

DIMENSIONS (H X W X D)	
EXTERIOR, WITH PEDESTAL STYLE BASE:	
47-3/4" x 96" x 44-1/16"	
(1213mm x 2438mm x 1121mm)	
well dimensions (w x l x d):	
27-3/16" x 93-5/16" x 4-1/2"	
(690mm x 2370mm x 114mm)	

ELECTRICAL					
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	
120/208-240 (UL)	1	50/60	24.0	5.2	
at 208	1	50/60	24.0	5.2	BARE END, NO PLUG
at 240	1	50/60	24.0	5.2	
230 (CE)	1	50/60	24.3	5.6	
230	1	50/60	24.7	5.7	BARE END, NO PLUG

PAN CONFIGURATION	*		
PAN SIZE	DIMENSIONS		
FULL-SIZE & ONE-THIRD**:	12" x 20" x 2-1/2" (GN 1/1)	7	
	12" x 6" x 2-1/2" (GN 1/3)	7	
HALF-SIZE & ONE-THIRD**:	12" x 10" x 2-1/2" (GN 1/2)	14	
	12" x 6" x 2-1/2" (GN 1/3)	7	
FULL-SIZE SHEET PANS:	18" x 26" x 1"	4	
MAX. CAPACITY/VOLUME:	112 lbs (51 kg)		
	70 qts (84 L)		
* Pans are not included with display case.			

- \*\* Will also accept 4" (100mm) deep pans.

### **SPECIFICATIONS**

- Fourteen (14) overhead lights in three (3) light zones.
- Three (3) base heat zones with three (3) adjustable thermostats with a range of 1 through 10, and three (3) heat-on indicator lights.
- Four (4) tinted, reflective, tempered glass sliding doors on operator side.
- Two (2) 10" x 36" (254mm x 914mm) operator-side work shelves.

OPTIONS & ACCESSORIES			
☐ <b>BUTTING KIT</b> CONT	CACT FACTORY	PLATFORM SCALE	
☐ CARVING STATION	5001874	☐ LEFT-SIDE	5005338
$\square$ GAUGE, INTERIOR AMBIENT TEMP.	GU-33384	☐ RIGHT-SIDE	5005337
$\ \square$ GLASS, TEMPERED END PANE, BRONZE K	IT 5008531	SHEET PAN DIVIDER BAR PACKAGE	
☐ INDEPENDENT ELECTRICAL OUTLET	5001781	☐ FULL-SERVICE CASES	5002805
PANEL KIT, SYSTEM		☐ SELF-SERVICE LEFT-SIDE OR RIGHT-SIDE OF CASES	5002806
☐ BRUSHED STAINLESS STEEL	5005146	☐ TEMPERATURE PROBE	5004918
☐ CUSTOM COLOR	5005149	☐ THERMOSTAT GUARD COVER PLATE	5007660



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY